

5 STAGE REVERSE OSMOSIS SYSTEM



R05

Part Number: 500028

FEATURES

- **FILTRATION PACKAGE**
 - **Stage 1:** Sediment Filter removes particulates down to 5 microns.
 - **Stage 2 & 3:** Carbon Block Filter removes chlorine taste and odors.
 - **Stage 4:** High Production 24 GPD TFC Membrane rejects impurities down to 1/10,000th of a micron.
 - **Stage 5:** Final filter for enhancing water quality and taste.
- Adapt-A-Valve for easy installation.
- Chrome Air Gap faucet.
- Color coded tubing for ease of installation and troubleshooting
- 3- Gallon Metal water storage tank

The R05 from Watts Pure Water produces water that rivals and often exceeds the quality of the bottled water found in supermarkets. Additionally, it provides a welcome replacement to the inconvenience and expense of delivered water.

VERSATILITY

- Space saving design installs under sink or in limited space.
- Adapt-A-Valve easily connects to water source.
- Can be connected to refrigerator ice maker.

RELIABILITY

- Advanced design uses patented technology and high quality components to assure years of continuous operation with trouble free performance.
- One Year Warranty
- **Watts Pure Water Reverse Osmosis System** is backed by Watts 130 year reputation of excellence.

PERFORMANCE

- Produces up to 24 gallons of high quality water per day.
- NSF tested and Certified to Standard 58.
- System goes well beyond basic water filtration and typical “pitcher” or “end-of-tap” filters.
- Reduces a long list of harmful contaminants. Including Lead, Arsenic, Perchlorate and more.



System tested and certified by NSF International against NSF/ANSI Standard 58. Refer to PDS for specific performance claims.

5 STAGE REVERSE OSMOSIS SYSTEM

PERFORMANCE

Element	Average In	Average Effect	% Reduction
Arsenic (Pentavalent)	334.615 ug/L	5.0385 ug/L	98.40%
Barium	10.2 mg/L	0.13 mg/L	98.70%
Cadmium	0.031 mg/L	0.0001 mg/L	99.70%
Chromium (Hexavalent)	0.30 mg/L	0.006 mg/L	98.00%
Chromium (Trivalent)	0.30 mg/L	.003 mg/L	99.00%
Copper	3.0 mg/L	0.04 mg/L	98.70%
Cysts	222,077 mg/L	10 mg/L	99.99%
Cryptosporidium	222,077 mg/L	10 mg/L	99.99%
Entamoeba	222,077 mg/L	10 mg/L	99.99%
Fluoride	8.0 mg/L	0.33 mg/L	95.90%
Giardia	222,077 mg/L	10 mg/L	99.99%
Lead	0.15 mg/L	0.004 mg/L	97.30%
Perchlorate	0.10 mg/L	0.003 mg/L	97.00%
Radium 226/228	25 pCi/L	5 pCi/L	80.00%
Selenium	0.10 mg/L	<0.001 mg/L	99.00%
TDS (Total Dissolved Solids)	765 mg/L	24 mg/L	96.80%
Turbidity	81 NTU	0.15 NTU	99.80%
Toxoplasma	222,077 mg/L	10 mg/L	99.99%

OPERATION PARAMETERS

Operating Temperatures	Minimum 40°F (4.4°C)	Maximum 100°F (37.8°C)
Operating Pressure	Minimum 40 psi (2.80 kg/cm ²)	Maximum 85 psi (6.0 kg/cm ²)
pH Parameters	Minimum 2	Maximum 11
Iron (Fe)		Maximum 1.0 ppm
TDS (Total Dissolved Solids)		Maximum 2000 ppm
Turbidity		Maximum 5 NTU

SYSTEM MAINTENANCE

Stage	Filter	Frequency	Part #
1	5-Micron Sediment	6 Months	104017
2 & 3	5-Micron Carbon Block	6 Months	101009
4	Membrane	1-3 Years	110009
5	Final Filter GAC 10"	1 year	100017

For more information please
call your authorized Watts representative

Jalovesi Oy
PL 1
00661 Helsinki

info@jalovesi.fi
www.jalovesi.fi